



PISTON INTAKE

## Piston Intake

Elkhart offers piston intake valves in your choice of materials. All piston valves include a variety of features to make your job easier: folding hand-wheel spinner, durable urethane seat, 4½" waterway, ¾" bleeder valve, adjustable relief/dump valve (75 to 250 psi) and a red urethane enamel finish.



APPLIANCES

4-13

HOSE CONNECTION (Inches)											TRUCK CONNECTION (Inches)			MATERIAL / TRIM		DIMENSIONS		MODEL	FIGURE
Female**				Male				Storz**		Female*			Brass	Elk-O-Lite®	Length	Weight			
3½	4	4½	5	3½	4	4½	5	6	4	5	4½	5	6	Chrome-plated	Hard Anodized	(Inches)	(Lbs.)		
o	o	o	o	o	o	o	o	o	o	o	o	o	s	•	•	11.4	22.5	9786	1
o	o	o	o	o	o	o	o	o	o	o	o	o	s	•	•	11.4	63.5	9787	2

KEY s = standard o = option

\* Swivel

\*\* Free swivel

Figure 1



Fig. 1

Figure 2



Fig. 2

### ADDITIONAL INFORMATION



• While many piston intake valves have the common issue of corrosion, resulting in minor leaks to complete failure — depending on service conditions and water supply; Elkhart's 9786 piston intake valve offers a solution. The replaceable anode electrolytically decomposes, while inhibiting the metal breakdown of the piston intake valve.

### THREADS

All fireground connections are NHT unless otherwise specified. See index T-12 for optional base threads.