

Ball Shut-offs & Playpipes

Elkhart Brass Ball Shut-offs and Playpipes are designed and constructed for rugged use and reliable performance as well as an excellent foundation for your break-apart nozzle needs using either smooth bore or fog nozzles. Elkhart Brass Ball Shut-offs and Playpipes are available with a variety of options, including built-in smooth bores which can be used with a fog nozzle tip for maximum versatility.



HANDLINE NOZZLES







BALL SHUT-OFFS & PLAYPIPES

BALL SHUT-OFFS & PLAYPIPES

Inlet Size	Outlet Size	WATERWAY SIZE	AVAILABLE INTEGRAL SMOOTH BORE DISCHARGE SIZE	BALL TYPES	SEAT	DRIVE	GRIP	BASE					HANDLE		MATERIAL		MODEL	FIGURE			
								TYPE			LENGTH		Tab	Horseshoe	Brass	Elk-O-Lite®					
								Rigid	Swivel	Free Swivel	Long	Short									
1"	1"	1"		Single Cutaway		Single Adjustable				Rigid				Tab					SB-275	2	
		1 3/8"		Double Cutaway		Double Non-Adjustable				Swivel				Horseshoe					SB-275-A	2	
		1 1/2"		Full Round		Single				Free Swivel				Brass					SB-275-AT	1	
		1 3/4"		Single Adjustable		Double				Long				Elk-O-Lite®					SB-275-G	2	
		1/2"		Pistol Grip		Single				Short										SB-275-GA	2
		7/8"		Playpipe		Double														SB-275-GAT	1
1.5"	1.5"	1 1/4"		Ladderhook						Rigid				Tab					LB-275	2	
										Swivel				Horseshoe					LB-275-A	2	
										Free Swivel				Brass					LB-275-GA	2	
										Long										B-275	2
										Short										B-275-A	2
																				B-275-GA	2
																				B-375-A	2
																				B-375-AT	1
																				B-375-GA	2
																				B-375-GAT	1
2.5"	1.5"																		DB-275		
																			DB-275-A		
																			DB-275-GA		
																			DB-375-A		
																			DB-375-GA		
																			DB-375-AT		
																			DB-375-GAT		
																				B-278	4
																				B-278-AT	4
																				B-278-L	4
																				B-877-A*	
																				279-L	3
																		279-LA	3		
																		211T			
2.5"	2.5"																		JB-275		
																			JB-275-A		
																			JB-275-GA		

Key s = standard o = option
 *B-278 (without ladderhook) + ST-190-BA (Triple Stack Tip)

BALL SHUT-OFFS AND PLAYPIPES CONFIGURATIONS

Figure 1	 <p>INTEGRAL SMOOTH BORE (Shown with optional pistol grip)</p> <p style="text-align: right;"><i>Fig. 1</i></p>
Figure 2	 <p>TYPICAL BALL SHUT-OFF (Shown with optional pistol grip)</p> <p style="text-align: right;"><i>Fig. 2</i></p>
Figure 3	 <p>PLAYPIPE WITHOUT SHUT-OFF</p> <p style="text-align: right;"><i>Fig. 3</i></p>
Figure 4	 <p>PLAYPIPE WITH SHUT-OFF</p> <p style="text-align: right;"><i>Fig. 4</i></p>

Figures depict general product types only and are not intended to be inclusive of all product features.

DOUBLE CUT-AWAY

Ball is hydraulically balanced for a smooth transition from closed to open and open to closed.

FULL ROUND

Ball has a solid bore for optimal flow characteristics and stream quality — particularly for smooth bores and shut-offs with built-in smooth bores.

SINGLE CUT-AWAY

Combines the features of smooth operation and excellent stream quality.

OPTIONS

COLORS



Color options available for pistol grip and handle. Ball shut-offs standards are a rough chrome handle and natural Elk-O-Lite® pistol grip.

HANDLES

TAB



HORSESHOE



BASES



LONG



SHORT

THREADS

All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.